

0-2.0% Ethane, 0-2.0% Hydrogen 0-2.5% Methane 0-23.5% Oxygen Balance N2**50013**

Label 2.2 : Non flammable, non toxic gas.

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Trade name : 0-2.0% Ethane, 0-2.0% Hydrogen 0-2.5% Methane 0-23.5% Oxygen Balance N2
MSDS Nr : 50013
Use : Calibration of Monitoring and Research Equipment
Company identification : Air Liquide Australia Limited
380 St. Kilda Road
Melbourne 3004 Australia
Tel: + 61 3 9697 9888
Fax: + 61 3 9690 7107
ALAEquiries@AirLiquide.com
Emergency phone nr : 1800 812 588

2 HAZARDS IDENTIFICATION

Hazard classification : Not Classified as Hazardous according to NOHSC criteria. Classified as Dangerous Goods by the criteria of the ADG code.
Hazards identification : Compressed gas.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Preparation : Preparation.
Components : This product is not hazardous but contains hazardous components.

Substance name	Contents	CAS No	EC No	Annex No	Classification
Carbon monoxide	: Between 0.0001 and 1 %	630-08-0	211-128-3	006-001-00-2	F+; R12 Repr. Cat. 1; R61 T; R23-48/23
Ethane	: Between and 2 %	74-84-0	200-814-8	601-002-00-X	F+; R12
Hydrogen	: Between and 2 %	1333-74-0	215-605-7	001-001-00-9	F+; R12
Oxygen	: Between and 23.5	7782-44-7	231-956-9	008-001-00-8	O; R8
Nitrogen	:	7727-37-9	231-783-9	-----	

4 FIRST AID MEASURES

- Inhalation : Not hazardous.
- Skin/eye contact : No effect on living tissue.
- Ingestion : Ingestion is not considered a potential route of exposure.

5 FIRE-FIGHTING MEASURES

Flammable class : Non flammable.
Specific hazards : Exposure to fire may cause containers to rupture/explode.
Supports combustion.
Hazardous combustion products : No data available.
None.

0-2.0% Ethane, 0-2.0% Hydrogen 0-2.5% Methane 0-23.5% Oxygen Balance N2**50013****5 FIRE-FIGHTING MEASURES (continued)****Extinguishing media****- Suitable extinguishing media** : All known extinguishants can be used.**Specific methods** : If possible, stop flow of product.
Move away from the container and cool with water from a protected position.**Special protective equipment for fire fighters** : None.**6 ACCIDENTAL RELEASE MEASURES****Personal precautions** : None necessary.**7 HANDLING AND STORAGE****Storage** : Keep container below 50°C in a well ventilated place.**Handling** : Open valve slowly to avoid pressure shock.
Suck back of water into the container must be prevented.
Do not allow backfeed into the container.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Refer to supplier's container handling instructions.**8 EXPOSURE CONTROLS/PERSONAL PROTECTION****Personal protection** : None necessary.**Occupational Exposure Limits** : Carbon monoxide : TLV[©] -TWA [ppm] : 25**9 PHYSICAL AND CHEMICAL PROPERTIES****Physical state at 20 °C** : Compressed gas.**Colour** : Colourless.**Odour** : Odourless.**Relative density, gas (air=1)** : Lighter or similar to air.**Solubility in water [mg/l]** : Not known.**10 STABILITY AND REACTIVITY****Stability and reactivity** : Stable under normal conditions.**11 TOXICOLOGICAL INFORMATION****Toxicity information** : No toxicological effects from this product.**12 ECOLOGICAL INFORMATION****Ecological effects information** : No ecological damage caused by this product.**Effect on ozone layer** : None.**Global warming potential [CO₂=1]** : Contains greenhouse gas(es) not covered by 842/2006/EC

0-2.0% Ethane, 0-2.0% Hydrogen 0-2.5% Methane 0-23.5% Oxygen Balance N2**50013****13 DISPOSAL CONSIDERATIONS**

General : None.
Disposal method : Consult supplier for specific recommendations.

14 TRANSPORT INFORMATION

UN No. : 1956
Labelling ADG : Label 2.2 : Non flammable, non toxic gas.
H.I. nr : 20
Proper shipping name : COMPRESSED GAS, N.O.S. (Nitrogen, Carbon monoxide)
HAZCHEM - Emergency Action Code : 2TE
: 2 = *Fine water spray.*
: T = *Recommended personal protective equipment : Full fire kit and breathing apparatus.*
: *Appropriate measures : dilute.*
: *E = There may be a public safety hazard outside the immediate area of the incident, and that the following actions should be considered :*
: 1. *People should be warned to stay indoors with all doors and windows closed, preferably in rooms upstairs and facing away from the incident. Ignition sources should be eliminated and any ventilation stopped.*
: 2. *Effects may spread beyond the immediate vicinity. all non-essential personnel should be instructed to move at least 250 metres away from the incident.*
: 3. *Police and fire brigade incident commanders should consult each other and with a product expert, or with a source of product expertise.*
: 4. *The possible need for subsequent evacuation should be considered, but it should be remembered that in most cases it will be safer to remain in a building than to evacuate.*
- ADG Class : 2
- ADG Classification code : 1 A
Other transport information : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers :
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.
- Compliance with applicable regulations.

15 REGULATORY INFORMATION

EC Labelling : Not classified as dangerous preparation/substance.
Symbol(s) : None.
R Phrase(s) : None.
S Phrase(s) : None.

16 OTHER INFORMATION

Receptacle under pressure.
Ensure all national/local regulations are observed.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.



MATERIAL SAFETY DATA SHEET

Page : 4

Revised edition no : 1

Date : 11 / 5 / 2010

Supersedes : 0 / 0 / 0

0-2.0% Ethane, 0-2.0% Hydrogen 0-2.5% Methane 0-23.5% Oxygen Balance N2

50013

16 OTHER INFORMATION (continued)

End of document