

Safety Data Sheet



0-999ppm DICHLORODIFLUOROMETHANE (R12), 0-23.5% OXYGEN
in NITROGEN

Date of first issue: 16/08/2010

Revised date: 23/11/2016

Supersedes: 26/11/2012

Version: 2.1

SDS reference: 50040-R12

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SDS no : 50040-R12

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use
Test gas/Calibration gas
Laboratory use
Contact supplier for more information on uses

Uses advised against : Consumer use

1.3. Details of the supplier of the safety data sheet

Company identification : Air Liquide Australia Limited
Level 9 / 380 St. Kilda Road
3004 Melbourne VIC Australia
+61 3 9697 9888
ALAEquiries@AirLiquide.com

1.4. Emergency telephone number

Emergency telephone number : 1800 812 588

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to WHS Regulation

Physical hazards Gases under pressure : Compressed gas H280

2.2. Label elements

Classification according to WHS Regulation

Hazard pictograms :



GHS04

Signal word : Warning

Hazard statements : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements

- Storage : P403 - Store in a well-ventilated place



2.3. Other hazards

: None

SECTION 3: Composition/information on ingredients

3.1. Substance : Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to WHS Regulation
Nitrogen	(CAS No) 7727-37-9 (EC no) 231-783-9 (EC index no) (REACH-no) *1	Balance	Press. Gas (Comp.), H280
Oxygen	(CAS No) 7782-44-7 (EC no) 231-956-9 (EC index no) 008-001-00-8 (REACH-no) *1	<= 23.5	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Dichlorodifluoromethane (R12)	(CAS No) 75-71-8 (EC no) 200-893-9 (EC index no) (REACH-no) 01-2119966166-30	<= 0.0999	Press. Gas (Liq.), H280 Aquatic Chronic 3, H412 Ozone 1, H420

Full text of R- and H-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*2: Registration deadline not expired.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Adverse effects not expected from this product
- Skin contact : Adverse effects not expected from this product
- Eye contact : Adverse effects not expected from this product
- Ingestion : Ingestion is not considered a potential route of exposure

4.2. Most important symptoms and effects, both acute and delayed

: No effect on living tissue
 Refer to section 11

4.3. Indication of any immediate medical attention and special treatment needed

: None

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog
- Unsuitable extinguishing media : Do not use water jet to extinguish

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Supports combustion
 Exposure to fire may cause containers to rupture/explode
- Hazardous combustion products : None

5.3. Advice for fire-fighters

Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems If possible, stop flow of product Use water spray or fog to knock down fire fumes if possible Move containers away from the fire area if this can be done without risk
Special protective equipment for fire fighters	: Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters
Hazchemcode	: 2TE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- : Try to stop release
- Act in accordance with local emergency plan
- Stay upwind

6.2. Environmental precautions

- : None

6.3. Methods and material for containment and cleaning up

- : None

6.4. Reference to other sections

- : See also sections 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product	: The substance must be handled in accordance with good industrial hygiene and safety procedures Only experienced and properly instructed persons should handle gases under pressure Consider pressure relief device(s) in gas installations Ensure the complete gas system was (or is regularly) checked for leaks before use Do not smoke while handling product Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt Do not breathe gas Avoid release of product into atmosphere.
-------------------------	---



0-999ppm
DICHLORODIFLUOROMETHANE
(R12), 0-23.5% OXYGEN in
NITROGEN

SDS Ref.: 50040-R12

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions
- Do not allow backfeed into the container
- Protect cylinders from physical damage; do not drag, roll, slide or drop
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use
- If user experiences any difficulty operating cylinder valve discontinue use and contact supplier
- Never attempt to repair or modify container valves or safety relief devices
- Damaged valves should be reported immediately to the supplier
- Keep container valve outlets clean and free from contaminants particularly oil and water
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment
- Close container valve after each use and when empty, even if still connected to equipment
- Never attempt to transfer gases from one cylinder/container to another
- Never use direct flame or electrical heating devices to raise the pressure of a container
- Do not remove or deface labels provided by the supplier for the identification of the cylinder contents
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.

7.2. Conditions for safe storage, including any incompatibilities

- : Observe all regulations and local requirements regarding storage of containers
- Containers should not be stored in conditions likely to encourage corrosion
- Container valve guards or caps should be in place
- Containers should be stored in the vertical position and properly secured to prevent them from falling over
- Stored containers should be periodically checked for general condition and leakage
- Keep container below 50°C in a well ventilated place
- Store containers in location free from fire risk and away from sources of heat and ignition
- Keep away from combustible materials.

7.3. Specific end use(s)

- : None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

0-999ppm DICHLORODIFLUOROMETHANE (R12), 0-23.5% OXYGEN in NITROGEN

OEL : Occupational Exposure Limits

Australia	TWA (mg/m ³)	4950 mg/m ³ Dichlorodifluoromethane
	TWA (ppm)	1000 ppm Dichlorodifluoromethane

Dichlorodifluoromethane (R12) (75-71-8)

DNEL: Derived no effect level (Workers)

Long-term - systemic effects, inhalation	1656.6 mg/m ³
--	--------------------------

Dichlorodifluoromethane (R12) (75-71-8)

PNEC: Predicted no effect concentration

Aqua (freshwater)	0.019 mg/l
Aqua (marine water)	0.0019 mg/l

8.2. Exposure controls

8.2.1. Appropriate engineering controls

- : Provide adequate general and local exhaust ventilation
- Systems under pressure should be regularly checked for leakages
- Consider work permit system e.g. for maintenance activities

8.2.2. Individual protection measures, e.g. personal protective equipment

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected



- Eye/face protection : Wear safety glasses with side shields
Standard EN 166 - Personal eye-protection
- Skin protection
 - Hand protection : Wear working gloves when handling gas containers
Standard EN 388 - Protective gloves against mechanical risk
 - Other : Wear safety shoes while handling containers
Standard EN ISO 20345 - Personal protective equipment - Safety footwear
- Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask
- Thermal hazards : None necessary

8.2.3. Environmental exposure controls

: None necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance

- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Mixture contains one or more component(s) which have the following colour(s):
Colourless.

Odour : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.
Mixture contains one or more component(s) which have the following odour(s):
Ethereal.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH value : Not applicable for gas-mixtures.

Molar mass : Not applicable for gas-mixtures.

Melting point : Not applicable for gas-mixtures.

Boiling point : Not applicable for gas-mixtures.

Flash point : Not applicable for gas-mixtures.

Evaporation rate (ether=1) : Not applicable for gas-mixtures.

Flammability range : Non flammable.

Vapour pressure [20°C] : Not applicable.

Vapour pressure [50°C] : Not applicable.

Relative density, gas (air=1) : Lighter or similar to air.

Solubility in water : No data available

Partition coefficient n-octanol/water [log Kow] : Not applicable for gas-mixtures.

Auto-ignition temperature : Non flammable.

Viscosity [20°C] : Not applicable.

Explosive Properties : Not applicable

Oxidising Properties : Not applicable

9.2. Other information

Other data : None

SECTION 10: Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below

10.2. Chemical stability

: Stable under normal conditions

10.3. Possibility of hazardous reactions

: None

10.4. Conditions to avoid

: None

10.5. Incompatible materials

: None

10.6. Hazardous decomposition products

: None

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : No toxicological effects from this product

Skin corrosion/irritation : No known effects from this product

Serious eye damage/irritation : No known effects from this product

Respiratory or skin sensitisation : No known effects from this product

Germ cell mutagenicity : No known effects from this product

Carcinogenicity : No known effects from this product

Toxic for reproduction : Fertility : No known effects from this product

Toxic for reproduction : unborn child : No known effects from this product

STOT-single exposure : No known effects from this product

STOT-repeated exposure : No known effects from this product

Aspiration hazard : Not applicable for gases and gas mixtures

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.

12.2. Persistence and degradability

Assessment : No data available.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : No data available.

12.5. Results of PBT and vPvB assessment

**AIR LIQUIDE**

0-999ppm
DICHLORODIFLUOROMETHANE
(R12), 0-23.5% OXYGEN in
NITROGEN

SDS Ref.: 50040-R12

Assessment : Not classified as PBT or vPvB

12.6. Other adverse effectsEffect on ozone layer : None
Effect on the global warming : Contains greenhouse gas(es) not covered by Regulation (EC) 842/2006.**SECTION 13: Disposal considerations****13.1. Waste treatment methods**Contact supplier if guidance is required
May be vented to atmosphere
Do not discharge into any place where its accumulation could be dangerous
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods

List of hazardous waste codes (from Commission Decision 2001/118/EC) : 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04

13.2. Additional information

: None

SECTION 14: Transport information**14.1. UN number**

UN-No. : 1956

14.2. UN proper shipping name**Transport by road/rail (ADR/RID)** : COMPRESSED GAS, N.O.S. (Nitrogen, Dichlorodifluoromethane (R12))**Transport by air (ICAO-TI / IATA-DGR)** : Compressed gas, n.o.s. (Nitrogen, Dichlorodifluoromethane (R12))**Transport by sea (IMDG)** : COMPRESSED GAS, N.O.S. (Nitrogen, Dichlorodifluoromethane (R12))**14.3. Transport hazard class(es)****Labelling**

2.2 : Non-flammable, non-toxic gases

Transport by road/rail (ADG)Class : 2
Hazchemcode : 2TE
Hazard identification number : 20
Tunnel Restriction : E - Passage forbidden through tunnels of category E**Transport by air (ICAO-TI / IATA-DGR)**

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

**14.4. Packing group**

Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user**Packing Instruction(s)**

Transport by road/rail (ADR/RID) : P200
Transport by air (ICAO-TI / IATA-DGR)
Passenger and Cargo Aircraft : 200
Cargo Aircraft only : 200
Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency
Before transporting product containers:
- Ensure there is adequate ventilation
- Ensure that containers are firmly secured
- Ensure cylinder valve is closed and not leaking
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted
- Ensure valve protection device (where provided) is correctly fitted.

HAZCHEMCODE : 2TE

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

**AIR LIQUIDE**

0-999ppm
DICHLORODIFLUOROMETHANE
(R12), 0-23.5% OXYGEN in
NITROGEN

SDS Ref.: 50040-R12

Training advice : Receptacle under pressure.

Full text of H-statements

Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Ox. Gas 1	Oxidising Gases, Category 1
Ozone 1	Hazardous to the ozone layer — category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H412	Harmful to aquatic life with long lasting effects
H420	Harms public health and the environment by destroying ozone in the upper atmosphere
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R59	Dangerous for the ozone layer
R8	Contact with combustible material may cause fire
N	Dangerous for the environment
O	Oxidising

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out
Details given in this document are believed to be correct at the time of going to press
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted

End of document