

**14.3-99% METHANE, 0-50% CARBON DIOXIDE in NITROGEN**
**50051**


Label 2.1 : flammable gas.

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Trade name** : 14.3-99% METHANE, 0-50% CARBON DIOXIDE in NITROGEN  
**MSDS Nr** : 50051  
**Use** : Calibration.  
**Company identification** : Air Liquide Australia Limited  
 Level 9 / 380 St. Kilda Road  
 Melbourne VIC 3004 Australia  
 Tel: + 61 3 9697 9888  
 Fax: + 61 3 9690 7107  
 ALAEnquiries@AirLiquide.com  
**Emergency phone nr** : 1800 812 588

**2 HAZARDS IDENTIFICATION**

**Hazard classification** : Not classified as hazardous according to NOHSC criteria.  
 Classified as a dangerous good by the criteria of the ADG code.  
**Hazards identification** : Compressed gas.  
 Extremely flammable.  
**R Phrase(s)** : R12 : Extremely flammable.  
**S Phrase(s)** : S9 : Keep container in a well-ventilated place. - S16 : Keep away from sources of ignition - No smoking. - S33 : Take precautionary measures against static discharges.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Preparation		Preparation.				
Substance name		Contents	CAS No	EC No	Annex No	Classification
Methane	:	>= 14.3 <= 99 %	74-82-8	200-812-7	601-001-00-4	F+; R12
Carbon dioxide	:	<= 50 %	124-38-9	204-696-9	----	
Nitrogen	:	balance	7727-37-9	231-783-9	----	

**4 FIRST AID MEASURES**

**First aid measures**  
**- Inhalation** : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.  
 In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.  
 Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.



# MATERIAL SAFETY DATA SHEET

Page : 2

Revised edition no : 1

Date : 17 / 8 / 2010

Supersedes : 0 / 0 / 0

## 14.3-99% METHANE, 0-50% CARBON DIOXIDE in NITROGEN

50051

### 5 FIRE-FIGHTING MEASURES

- Specific hazards** : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products** : Incomplete combustion may form carbon monoxide.
- Extinguishing media**
- **Suitable extinguishing media** : All known extinguishants can be used.
- Specific methods** : If possible, stop flow of product.  
Move away from the container and cool with water from a protected position.  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
- Special protective equipment for fire fighters** : In confined space use self-contained breathing apparatus.

### 6 ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
Evacuate area.  
Ensure adequate air ventilation.  
Eliminate ignition sources.
- Environmental precautions** : Try to stop release.
- Clean up methods** : Ventilate area.

### 7 HANDLING AND STORAGE

- Storage** : Segregate from oxidant gases and other oxidants in store.  
Keep container below 50°C in a well ventilated place.
- Handling** : Ensure equipment is adequately earthed.  
Suck back of water into the container must be prevented.  
Purge air from system before introducing gas.  
Do not allow backfeed into the container.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
Keep away from ignition sources (including static discharges).  
Refer to supplier's container handling instructions.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Personal protection** : Ensure adequate ventilation.  
Do not smoke while handling product.
- Occupational Exposure Limits** : Carbon dioxide : ILV (EU) - 8 H - [mg/m<sup>3</sup>] : 9000  
Carbon dioxide : ILV (EU) - 8 H - [ppm] : 5000  
Carbon dioxide : TLV<sup>©</sup> -TWA [ppm] : 5000  
Carbon dioxide : TLV<sup>©</sup> -STEL [ppm] : 30000

### 9 PHYSICAL AND CHEMICAL PROPERTIES

- Physical state at 20 °C** : Gas.
- Colour** : Colourless gas.
- Odour** : None.
- Molecular weight** : 16
- Melting point [°C]** : -182
- Boiling point [°C]** : -161

**14.3-99% METHANE, 0-50% CARBON DIOXIDE in  
NITROGEN****50051****9 PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Critical temperature [°C]	: -82
Vapour pressure [20°C]	: Not applicable.
Relative density, gas (air=1)	: 0.6
Relative density, liquid (water=1)	: 0.42
Solubility in water [mg/l]	: 26
Flammability range [vol% in air]	: 5 to 15
Auto-ignition temperature [°C]	: 595

**10 STABILITY AND REACTIVITY**

Hazardous decomposition products	: None.
Materials to avoid	: Can form explosive mixture with air. May react violently with oxidants. Air, Oxidiser.
Conditions to avoid	: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

**11 TOXICOLOGICAL INFORMATION**

Toxicity information	: No known toxicological effects from this product.
----------------------	---

**12 ECOLOGICAL INFORMATION**

Global warming potential [CO2=1]	: Contains greenhouse gas(es) not covered by 842/2006/EC
----------------------------------	--

**13 DISPOSAL CONSIDERATIONS**

General	: Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.
---------	---

**14 TRANSPORT INFORMATION**

UN No.	: 1954
• Labelling ADG, IMDG, IATA	



: Label 2.1 : flammable gas.

**Land transport**

H.I. nr	: 23
Proper shipping name	: COMPRESSED GAS, FLAMMABLE, N.O.S.
HAZCHEM - Emergency Action Code	: 2SE
	: 2 = Fine water spray. S = Risk of violent reaction or explosion. Recommended personal protective equipment : Full fire kit and breathing apparatus. Appropriate measures : dilute. E = There may be a public safety hazard outside the immediate area of the incident, and that the following actions should be considered : 1. People should be warned to stay indoors with all doors and windows closed, preferably in rooms upstairs and facing away from the incident. Ignition sources should be eliminated and any ventilation stopped.



# MATERIAL SAFETY DATA SHEET

Page : 4

Revised edition no : 1

Date : 17 / 8 / 2010

Supersedes : 0 / 0 / 0

## 14.3-99% METHANE, 0-50% CARBON DIOXIDE in NITROGEN

50051

### 14 TRANSPORT INFORMATION (continued)

2. Effects may spread beyond the immediate vicinity. all non-essential personnel should be instructed to move at least 250 metres away from the incident.
3. Police and fire brigade incident commanders should consult each other and with a product expert, or with a source of product expertise.
4. The possible need for subsequent evacuation should be considered, but it should be remembered that in most cases it will be safer to remain in a building than to evacuate.

- ADG Class : 2
- ADG Classification code : 1 F
- Packing Instruction(s) - General : P200

#### Sea transport

- IMO-IMDG code
- Proper shipping name : COMPRESSED GAS, FLAMMABLE, N.O.S.
- Class : 2.1
- IMO Packing group : P200
- Emergency Schedule (EmS) - Fire : F-D
- Emergency Schedule (EmS) - Spillage : S-U
- Instructions - Packing : P200

#### Air transport

- ICAO/IATA
- Proper shipping name : COMPRESSED GAS, FLAMMABLE, N.O.S.
- Class : 2.1
- Passenger and Cargo Aircraft : DO NOT LOAD IN PASSENGER AIRCRAFT.
- Cargo Aircraft only : Allowed.
- Packing instruction : 200

#### Other transport information

- : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
- Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
- Before transporting product containers :
  - Ensure that containers are firmly secured.
  - Ensure cylinder valve is closed and not leaking.
  - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
  - Ensure valve protection device (where provided) is correctly fitted.
  - Ensure there is adequate ventilation.
  - Compliance with applicable regulations.

### 15 REGULATORY INFORMATION

- EC Classification : F+; R12
- EC Labelling
- Symbol(s) : F+ : Extremely flammable
- R Phrase(s) : R12 : Extremely flammable.
- S Phrase(s) : S9 : Keep container in a well-ventilated place.  
S16 : Keep away from sources of ignition - No smoking.  
S33 : Take precautionary measures against static discharges.

### 16 OTHER INFORMATION

- Ensure all national/local regulations are observed.
- Ensure operators understand the flammability hazard.
- The hazard of asphyxiation is often overlooked and must be stressed during operator training.

#### Air Liquide Australia Limited

Level 9 / 380 St. Kilda Road Melbourne VIC 3004 Australia

Tel: + 61 3 9697 9888

Fax: + 61 3 9690 7107

ALAEquiries@AirLiquide.com

In case of emergency : 1800 812 588



# MATERIAL SAFETY DATA SHEET

Page : 5

Revised edition no : 1

Date : 17 / 8 / 2010

Supersedes : 0 / 0 / 0

**14.3-99% METHANE, 0-50% CARBON DIOXIDE in  
NITROGEN**

**50051**

## 16 OTHER INFORMATION (continued)

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

### DISCLAIMER OF LIABILITY

: Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Details given in this document are believed to be correct at the time of going to press. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

**End of document**