

## MATERIAL SAFETY DATA SHEET

**Product Name:**

**HYDROGEN containing Compressed  
Gas Mixture (Hydrogen > 2.5%)**

Issued: May 2014

Revision: 8

Page: 1 of 6



Label 2.1 : flammable  
gas.

### IDENTIFICATION

**Chemical Name:** Hydrogen, Nitrogen and Argon  
**Synonyms:** Air Liquide range including SST2, SST3, PUR1 & NOXAL some Arcal™ range  
**UN Number:** 1954  
**Poisons Schedule Number:** None Allocated  
**G.T. EPG. (Group Text. Emergency Procedure Guide):** AS 1678 2A1 or 2A2

**Use:** Welding applications.

### HAZARDS IDENTIFICATION

**Dangerous Goods Class and Subsidiary Risk:** 2.1  
**HSNO Classification:** 2.1.1A

**Hazard Statement:** Extremely flammable gas.  
Explosive; fire, blast or projection hazard.

**Precautionary Statements:** Read before label before use.  
Read material safety data sheet before use.  
Keep away from heat, sparks, open flames and hot surfaces.  
No smoking.  
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
Eliminate all ignition sources if safe to do so.  
Store in a well ventilated place.

### COMPOSITION

Ingredients	CAS Number	Proportion
Chemical Entity		
Hydrogen	1333-74-0	2.5% to 40%
Argon	7440-37-1	80% to 97.5%
Nitrogen	7727-37-9	60%

### FIRST AID MEASURES

#### Health Effects

##### Acute

Swallowed: Not applicable to gases.  
Eye: Not irritating to the eye.  
Skin: Not irritating to the skin.

**Issued: May 2014****Revision: 8****Page 2 of 6**

**Inhaled:** Hydrogen is non-toxic at normal temperature and pressure. By diluting the oxygen concentration in air below the level necessary to support life, it can act as an asphyxiant. Effects of oxygen deficiency are: 12-16%: breathing and pulse rate increased, muscular coordination slightly disturbed; 10-14%: emotional upset, abnormal fatigue, disturbed respiration; 6-10%: nausea and vomiting, collapse or loss of consciousness; below 6%: convulsive movements, possible respiratory collapse and death.

**Chronic**

Long term exposure to hydrogen has no known health effects. Prolonged exposure to an oxygen deficient atmosphere (below 18% oxygen in air) may affect the heart and nervous system.

**First Aid**Inhaled:

Call doctor. If victim is conscious: Move to uncontaminated area to breathe fresh air. Keep warm and quiet. If victim is unconscious: Move to uncontaminated area and give assisted respiration. When normal breathing is restored, treatment as above. Continued treatment should be symptomatic and supportive.

Skin Contact:

Remove contaminated clothing and shoes immediately.

Eye Contact:

If eyes become affected gently flood with tap water for at least 15 minutes, call doctor

**Advice to Doctor**

Advise doctor that victim has been exposed to an oxygen deficient atmosphere and exposed to acetylene which is a known anaesthetic.

**FIRE FIGHTING MEASURES****Flammability:**

Highly flammable. Spontaneously flammable in air. Avoid all ignition sources.

**Fire/Explosion Hazard:**

Hydrogen is highly flammable and burns with almost invisible flame. Container may rupture when heated. Move cylinders from fire if safe to do so. Cool cylinders with water from a protected location. If unable to keep cylinders cool, Evacuate Area.

**Extinguishing Media:**

Water fog or fine water spray.

**Hazchem Code:**

2SE

**Recommended Protective Clothing:**

Breathing apparatus need only be worn if the substance is involved in a fire or in confined space.

**ACCIDENTAL RELEASE MEASURES****Personal Protection:**

Personnel engaged in the movement of cylinders shall be provided with safety footwear and leather or PVC gloves. Full cover overalls and safety glasses recommended. In areas where equipment failure may cause an immediate high concentration of hydrogen, approved self-contained full face respiratory equipment should be readily available.

**Spills and Disposal:**

Ventilate area. Stop leak if it can be done without risk. Allow gas to dissipate to atmosphere. Evacuate Area.

**Issued: May 2014****Revision: 8****Page 3 of 6****Reference Guide:**

Standard SNZ HB 76:2008 Dangerous Goods – Initial Emergency Response Guide.

**General:**

Only experienced and properly instructed personnel should handle compressed gases. Cylinder contents and identification labels provided by the supplier must not be removed or defaced. Colour coding should not be the only criterion used for content identification.

**HANDLING AND STORAGE****Handling****Flammability:**

Highly flammable. Spontaneously flammable in air. Avoid all ignition sources.

**General:**

Only experienced and properly instructed personnel should handle compressed gases. Cylinder contents and identification labels provided by the supplier must not be removed or defaced. Colour coding should not be the only criterion used for content identification.

**Approved Handlers:**

Approved handlers are required if more than 100 m<sup>3</sup> is stored on site.

**Storage****Separation:**

Storage of compressed gas cylinders shall be in compliance with New Zealand regulations. Cylinders shall be stored in a cool, dry, well ventilated area out of direct sunlight and away from heat and ignition sources. No part of cylinders shall be exposed to temperatures above 50°C. Cylinders shall be stored upright on a level, fireproof floor, secure in position and protected from damage. Full cylinders shall be stored separately from empties. Segregate from oxidant gases and other oxidants in store. Avoid any contact with oil or grease particularly to the cylinder valve. Ensure equipment is adequately earthed. Suck back of water into the container must be prevented. Purge air from system before introducing gas. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Keep away from ignition sources (including static discharges). Cylinders should be moved by hand-truck or cart designed for that purpose.

**Spills and Disposal:**

Ventilate area. Stop leak if it can be done without risk. Allow gas to dissipate to atmosphere. Evacuate Area.

**EXPOSURE CONTROLS / PERSONAL PROTECTION****Exposure Standards:**

Hydrogen, Nitrogen and Argon are simple asphyxiants.

**Engineering Controls:**

Provide adequate local exhaust and dilution (general) ventilation and supply sufficient replacement air to maintain oxygen concentration above 18%.

**Personal Protection:**

Personnel engaged in the movement of cylinders shall be provided with safety footwear and leather or PVC gloves. Full cover overalls and safety glasses recommended. In areas where equipment failure may cause an immediate high concentration of hydrogen, approved self-contained full face respiratory equipment should be readily available.

**PHYSICAL AND CHEMICAL PROPERTIES****Physical Properties**

Appearance:	Colourless, Odourless, Tasteless	Flashpoint:	Not Applicable
Boiling Point:	Not Applicable	Flammability Limits (in Air):	4% to 75%
Vapour Pressure:	Not Applicable	Solubility in Water (at 0°C):	Not Applicable

**Other Properties**

Relative Density (at 15°C) (Air = 1):	0.8 to 1.37	Density of Gas (101.3 kPa, 15°C):	0.98 to 1.68
Molecular Weight:	Not Applicable	Critical Temperature:	Not Applicable

**STABILITY AND REACTIVITY****Flammability:**

Highly flammable. Spontaneously flammable in air. Avoid all ignition sources.

**Materials Compatibility:**

None recorded.

**TOXICOLOGY INFORMATION**

No known toxicological effects from this product.

**ECOLOGICAL INFORMATION**

No known ecological damage caused by this product.

**DISPOSAL CONSIDERATIONS**

Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous.

**TRANSPORT INFORMATION**

<b>UN Number:</b>	1954
<b>Proper Shipping Name:</b>	COMPRESSED GAS, FLAMMABLE, N.O.S (CONTAINS HYDROGEN, NITROGEN AND ARGON)
<b>Dangerous Goods Class and Subsidiary Risk:</b>	2.1
<b>Packing Group:</b>	Not applicable
<b>Hazchem Code:</b>	2SE

**Other Information:** Avoid transport on vehicles where the load is not separated from the driver's compartment.  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
Before transporting product containers:

- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure there is adequate ventilation.
- Compliance with applicable regulations.

**REGULATORY INFORMATION****ERMA Register Approval No:** HSR002532**HSNO Controls:** Compressed Gas Mixtures (Flammable) Group Standard 2006  
Hazardous Substances and New Organisms Act 1996**Approved Handlers:**Approved handlers are required if more than 100 m<sup>3</sup> is stored on site.**OTHER INFORMATION**

Gas mixture containing hydrogen is supplied in high pressure cylinders.

Cylinder Colour: AS 4484-2004 Peacock Blue PMS 5473C / Red PMS 485C / Pewter PMS 431U

Cylinder Valve Outlet: Industrial: AS 2473 Type 20, ALTOP

- References:
- . L'Air Liquide Gas Encyclopaedia - Elsevier Scientific Publishing Co. Amsterdam
  - . Cheminfo Database
  - . New Zealand Code for the Transport of Dangerous Goods by Road and Rail
  - . NHMRC Threshold Limit Values - Commonwealth Dept Health
  - . SAA Safe Storage and Handling Information Cards
  - . SAA Emergency Procedure Cards
  - . Matheson Gas Data Book, 6th Edition, Matheson 1980
  - . Canadian Liquid Air Montreal, Canada - Gas Products Safety Data Sheets
  - . AS 1894 Code of Practice for Safe Handling of Cryogenic fluids
  - . NZCIC Code of Practice – Preparation of Safety Data Sheets

**END MSDS**

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace in conjunction with other products.

If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company.

Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

This MSDS has been prepared in accordance with NZCIC Code of Practice – Preparation of Safety Data Sheets

**Air Liquide regional offices contact details on following page**

**Regional Offices****Auckland**

PO Box 12846  
19 Maurice Road  
Penrose  
Phone: 09 622 3888  
Fax: 09 622 3882

**Hamilton**

PO Box 10 394  
2 Tawn Place, Pukete  
Phone: 07 849 2969  
Fax: 07 348 9063

**Mt Maunganui**

89 Poturi Street, Tauriko  
Tauranga 3110  
Phone: 07 574 8475  
Fax: 07 574 8476

**Palmerston North**

PO Box 10 010  
5 Connolly Place  
Palmerston North  
Phone: 06 355 5216  
Fax: 06 354 7104

**Christchurch**

PO Box 16453  
7 Canterbury St  
Hornby  
Phone: 03 344 6033  
Fax: 03 344 6031

**Emergency 24hr Phone  
Number 0800 156 516**