Safety Data Sheet



0-0.48% HEXANE, 0-23.5% OXYGEN in NITROGEN

Date of first issue: 10/08/2010

Revised date: 04/10/2021

Supersedes version of: 09/09/2016

Version: 5.0

SDS reference: AL401

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SDS no : AL401

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional use for chemical analysis, calibration, (routine) quality control,

laboratory use, under controlled conditions

Uses advised against : Consumeruse.

Uses other than those listed above are not supported, contact your supplier for more

information on other uses.

1.3. Details of the supplier of the safety data sheet

Company identification : Air Liquide Australia Limited

Level 12 / 600 St. Kilda Road 3004 Melbourne VIC Australia

+61 3 9697 9888

ALAEnquiries@AirLiquide.com

1.4. Emergency telephone number

Emergency telephone number : 1800 812 588

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to WHS Regulation

Physical hazards Gases under pressure: Compressed gas H280

2.2. Label elements

Classification according to WHS Regulation

Hazard pictograms :



GHS0

Signal word : Warning

Hazard statements : H280 - Contains gas under pressure; may explode if heated..

Precautionary statements

- Storage: P403 - Store in a well-ventilated place..

2.3. Other hazards

: None.

EN (English)

Not classified as PBT or vPvB.

The substance/mixture has no endocrine disrupting properties.

Air Liquide Australia Limited Lev el 12 / 600 St. Kilda Road 3004 Melbourne VIC Australia +61 3 9697 9888 Reference number: AL401

1/9



Reference number: AL401

SECTION 3: Composition/information on ingredients

3.1. Substances : Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to WHS Regulation |
|----------|---|----------|---|
| Nitrogen | (CAS-No.) 7727-37-9 (EC-No.) 231-783-9 (EC Index-No.) (REACH-no) *1 | Balance | Press. Gas (Comp.), H280 |
| Oxy gen | (CAS-No.) 7782-44-7 (EC-No.) 231-956-9 (EC Index-No.) 008-001-00-8 (REACH-no) *1 | 0 – 23.5 | Ox. Gas 1, H270 Press. Gas (Comp.), H280 |
| n-hexane | (CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0 | 0 – 0.48 | Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 |

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
 Skin contact
 Adverse effects not expected from this product.
 Adverse effects not expected from this product.
 Eye contact
 Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

Product does not burn, use fire control measures appropriate for the surrounding fire.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

Special hazards arising from the substance or mixture

Specific hazards : Supports combustion.

Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

5.3. Advice for fire-fighters

^{*1:} Listed in Annex IV / V REACH, exempted from registration.

^{*3:} Registration not required: Substance manufactured or imported < 1t/y.



Reference number: AL401

Specific methods

: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Preventwater used in emergency cases from entering sewers and drainage systems.

If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters

: Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for

firefighters.

Hazchem Code : 2TI

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Act in accordance with local emergency plan.

Stay upwind.

6.2. Environmental precautions

: None

6.3. Methods and material for containment and cleaning up

: None.

6.4. Reference to other sections

: See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

 $: \ \, \text{The product must be handled in accordance with good industrial hygiene and safety} \\$

procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Do not smoke while handling product.

 $Use \ \ only\ properly\ specified\ equipment\ which\ is\ suitable\ for\ this\ product,\ its\ supply\ pressure\ and$

temperature. Contact your gas supplier if in doubt.
Use only oxygen approved lubricants and oxygen approved sealings.

Avoid suck back of water, acid and alkalis.

Do not breathe gas.

EN (English)

Avoid release of product into atmosphere.

Safe handling of the gas receptacle : R

Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.



Reference number: AL401

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.
 Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from

illing over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| 0-0.48% HEXANE, 0-23.5% OXYGEN in NITROGEN | | | | |
|--|-------------|----------|--|--|
| OEL : Occupational Exposure Limits | | | | |
| Australia | OES TWA [1] | 20 mg/m³ | | |
| | OES TWA [2] | 72 ppm | | |
| n-hexane (110-54-3) | | | | |
| OEL: Occupational Exposure Limits | | | | |
| Australia | OES TWA [1] | 72 mg/m³ | | |
| | OES TWA [2] | 20 ppm | | |

DNEL (Derived-No Effect Level): No data available.

PNEC (Predicted No-Effect Concentration): No data available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

: Provide a dequate general and local exhaust ventilation.

Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The

following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection : Wear safety glasses with side shields.

Standard EN 166 - Personal eye-protection - specifications

Skin protection

- Hand protection : Wear working gloves when handling gas containers.

EN (English)

Standard EN 388 - Protective gloves against mechanical risk.

- Other : Wear safety shoes while handling containers.

Standard ENISO 20345 - Personal protective equipment - Safety footwear.

Reference number: AL401

4/9



Reference number: AL401

Respiratory protection

: Gas filters may be used if all surrounding conditions e.g. type and concentration of the

contaminant(s) and duration of use are known.

Use gasfilters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

When indicated by a risk assessment, Respiratory Protective Equipment must be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.

Gas filters do not protect against oxygen deficiency.

Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN 136, full face masks. Self contained breathing apparatus is recommended, where unknown exposure may be

expected, e.g. during maintenance activities on installation systems.

 Thermal hazards : None necessary.

8.2.3. Environmental exposure controls

: None necessary.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas.

Mixture contains one or more component(s) which have the following colour(s):

Colourless.

Odour : Odourless.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH value : Not applicable for gas mixtures. Molarmass : Not applicable for gas mixtures. Meltingpoint : Not applicable for gas mixtures. Boiling point : Not applicable for gas mixtures. Flash point : Not applicable for gas mixtures. Evaporation rate (ether=1) : Not applicable for gas mixtures.

Flammability range : Non flammable. Vapour pressure [20°C] : Not applicable. Vapour pressure [50°C] : Not applicable.

Relative density, gas (air=1) : Lighter or similar to air. Solubility in water : No data available

Partition coefficient n-octanol/water [log Kow] : Not applicable for gas mixtures.

Auto-ignition temperature : Non flammable. Decomposition point [°C] : Not applicable. Viscosity [20°C] : Not applicable. **Explosive Properties** : Not applicable. Oxidising Properties : Not applicable.

Other information

Other data : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

: Data for mixture are not available



Reference number: AL401

10.2. **Chemical stability**

: Stable under normal conditions.

Possibility of hazardous reactions

: None

10.4. Conditions to avoid

: Avoid moisture in installation systems.

Incompatible materials 10.5.

: For additional information on compatibility refer to ISO 11114.

Hazardous decomposition products 10.6.

: Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity : No toxicological effects from this product.

Skin corrosion/irritation : No known effects from this product. : No known effects from this product. Serious eye damage/irritation : No known effects from this product. Respiratory or skin sensitisation Germ cell mutagenicity : No known effects from this product. : No known effects from this product. Carcinogenicity : No known effects from this product. Toxic for reproduction: Fertility Toxic for reproduction: unborn child : No known effects from this product. : No known effects from this product. STOT-single exposure STOT-repeated exposure : No known effects from this product.

: Not applicable for gases and gas mixtures. **Aspiration hazard**

Other information : The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

Bioaccumulativ e potential <u>12.3.</u>

Assessment : No data available.

Mobility in soil 12.4.

Assessment : No ecological damage caused by this product.

Results of PBT and vPvBassessment 12.5.

Assessment : Not classified as PBT or vPvB.

Other adverse effects

: No known effects from this product.

Effect on the ozone layer : None.

: No known effects from this product. Effect on global warming



Reference number: AL401

SECTION 13: Disposal considerations

Waste treatment methods

May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

amended)

Additional information

External treatment and disposal of waste should comply with applicable local and/or national

regulations

SECTION 14: Transport information

14.1. **UN** number

UN-No. : 1956

<u>14.2</u>. **UN proper shipping name**

: COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen) Transport by road/rail (ADR/RID)

Transport by air (ICAO-TI / IATA-DGR) : Compressed gas, n.o.s. (Nitrogen, Oxygen)

Transport by sea (IMDG) : COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)

Transport hazard class(es) <u>14.3.</u>

Labelling



2.2: Non-flammable, non-toxic gases

Transport by road/rail (ADG)

Class : 2 Hazchem Code : 2TE Hazard identification number : 20

Tunnel Restriction : E - Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2 Emergency Schedule (EmS) - Fire : F-C Emergency Schedule (EmS) - Spillage : S-V

Packing group

Transport by road/rail (ADR/RID) : Not applicable Transport by air (ICAO-TI/IATA-DGR) : Not applicable Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None. Transport by air (ICAO-TI/IATA-DGR) : None.



Reference number: AL401

Transport by sea (IMDG) : None.

Special precautions for user

No additional information availablePacking

Instruction(s)

Transport by road/rail (ADR/RID) : P200

Transport by air (ICAO-TI/IATA-DGR)

Passenger and Cargo Aircraft : 200 Cargo Aircraft only : 200 Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.

HAZCHEM CODE : 2TE

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Ensure all national/local regulations are observed.

Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

: ATE - Acute Toxicity Estimate. CLP - Classification Labelling Packaging Regulation; Regulation Abbreviations and acronyms

(EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. EINECS - European Inventory of Existing Commercial Chemical Substances. CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment. LC50 - Lethal Concentration to 50 % of a test population. RMM - Risk Management Measures. PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative. STOT-SE: Specific Target Organ Toxicity - Single Exposure. CSA - Chemical Safety Assessment. EN - European Standard. UN - United Nations. ADR -

European Agreement concerning the International Carriage of Dangerous Goods by Road. IATA - International Air Transport Association. IMDG code - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Rail. WGK - Water Hazard Class. STOT - RE: Specific Target Organ Toxicity - Repeated Exposure.

UFI: Unique Formula Identifier.

Trainingadvice : None

Full text of H-statements

Air Liquide Australia Limited Lev el 12 / 600 St. Kilda Road 3004 Melbourne VIC Australia +61 3 9697 9888

EN (English)

Reference number: AL401

8/9



Reference number: AL401

| Aquatic Chronic 2 | Hazardousto the aquatic environment — Chronic Hazard, Category 2 |
|--------------------|--|
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| H225 | Highly flammable liquid and vapour. |
| H270 | May cause or intensify fire; oxidiser. |
| H280 | Contains gas under pressure; may explode if heated. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361f | Suspected of damaging fertility. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| Ox. Gas 1 | Oxidising Gases, Category 1 |
| Press. Gas (Comp.) | Gases under pressure: Compressed gas |
| Repr. 2 | Reproductive toxicity, Category 2 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT RE 2 | Specific target organ toxicity — Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |

DISCLAIMER OF LIABILITY

 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Air Liquide Australia Limited