



# Safety Data Sheet

## 0-200PPM HYDROGEN SULPHIDE IN AIR

Date of first issue: 30/12/2016      Revised date: 02/12/2016      Supersedes: 09/11/2012      Version: 5.0  
SDS reference: AL404

**Warning**



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

SDS no : AL404

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use  
Test gas/Calibration gas  
Laboratory use  
Contact supplier for more information on uses

Uses advised against : Consumer use

#### 1.3. Details of the supplier of the safety data sheet

Company identification : Air Liquide Australia Limited  
Level 9 / 380 St. Kilda Road  
3004 Melbourne VIC Australia  
+61 3 9697 9888  
ALAEquiries@AirLiquide.com

#### 1.4. Emergency telephone number

Emergency telephone number : 1800 812 588

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to WHS Regulation

Physical hazards      Gases under pressure : Compressed gas      H280

#### 2.2. Label elements

##### Classification according to WHS Regulation

Hazard pictograms :



GHS04

Signal word :

Warning

Hazard statements :

H280 - Contains gas under pressure; may explode if heated.

Precautionary statements

- Storage : P410+P403 - Protect from sunlight. Store in a well-ventilated place

**2.3. Other hazards**

: None

**SECTION 3: Composition/information on ingredients**

**3.1. Substance** : Not applicable

**3.2. Mixture**

Name	Product identifier	%	Classification according to WHS Regulation
Nitrogen	(CAS No) 7727-37-9 (EC no) 231-783-9 (EC index no) (REACH-no) *1	Bal	Press. Gas (Comp.), H280
Oxygen	(CAS No) 7782-44-7 (EC no) 231-956-9 (EC index no) 008-001-00-8 (REACH-no) *1	18.9 - 23.1	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Hydrogen sulphide	(CAS No) 7783-06-4 (EC no) 231-977-3 (EC index no) 016-001-00-4 (REACH-no) *2	0 - 0.02	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335 Aquatic Acute 1, H400

Full text of R- and H-statements: see section 16

*Contains no other components or impurities which will influence the classification of the product.*

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*2: Registration deadline not expired.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

- Inhalation : Remove person to fresh air and keep comfortable for breathing  
Adverse effects not expected from this product
- Skin contact : Adverse effects not expected from this product  
Wash skin with plenty of water
- Eye contact : Adverse effects not expected from this product  
Rinse eyes with water as a precaution
- Ingestion : Ingestion is not considered a potential route of exposure  
Call a poison center or a doctor if you feel unwell

**4.2. Most important symptoms and effects, both acute and delayed**

: No effect on living tissue  
Refer to section 11

**4.3. Indication of any immediate medical attention and special treatment needed**

: None

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog  
Water spray  
Dry powder  
Foam
- Unsuitable extinguishing media : Do not use water jet to extinguish

**5.2. Special hazards arising from the substance or mixture**

- Specific hazards : Supports combustion  
Exposure to fire may cause containers to rupture/explode
- Hazardous combustion products : None

**5.3. Advice for fire-fighters**

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems  
If possible, stop flow of product  
Use water spray or fog to knock down fire fumes if possible  
Move containers away from the fire area if this can be done without risk
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask  
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters
- Hazchemcode : 2TE

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

- : Try to stop release  
Act in accordance with local emergency plan  
Stay upwind

**6.2. Environmental precautions**

- : Avoid release to the environment  
None

**6.3. Methods and material for containment and cleaning up**

- : None

**6.4. Reference to other sections**

- : See also sections 8 and 13  
For further information refer to section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

- Safe use of the product : The substance must be handled in accordance with good industrial hygiene and safety procedures  
Only experienced and properly instructed persons should handle gases under pressure  
Consider pressure relief device(s) in gas installations  
Ensure the complete gas system was (or is regularly) checked for leaks before use  
Do not smoke while handling product  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt  
Do not breathe gas  
Avoid release of product into atmosphere.

Safe handling of the gas receptacle : Refer to supplier's container handling instructions  
 Do not allow backfeed into the container  
 Protect cylinders from physical damage; do not drag, roll, slide or drop  
 When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders  
 Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use  
 If user experiences any difficulty operating cylinder valve discontinue use and contact supplier  
 Never attempt to repair or modify container valves or safety relief devices  
 Damaged valves should be reported immediately to the supplier  
 Keep container valve outlets clean and free from contaminants particularly oil and water  
 Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment  
 Close container valve after each use and when empty, even if still connected to equipment  
 Never attempt to transfer gases from one cylinder/container to another  
 Never use direct flame or electrical heating devices to raise the pressure of a container  
 Do not remove or deface labels provided by the supplier for the identification of the cylinder contents  
 Containers should be stored in the vertical position and properly secured to prevent them from falling over.

**7.2. Conditions for safe storage, including any incompatibilities**

: Observe all regulations and local requirements regarding storage of containers  
 Containers should not be stored in conditions likely to encourage corrosion  
 Container valve guards or caps should be in place  
 Containers should be stored in the vertical position and properly secured to prevent them from falling over  
 Stored containers should be periodically checked for general condition and leakage  
 Keep container below 50°C in a well ventilated place  
 Store containers in location free from fire risk and away from sources of heat and ignition  
 Keep away from combustible materials.

**7.3. Specific end use(s)**

: None.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

0-200PPM HYDROGEN SULPHIDE IN AIR		
OEL : Occupational Exposure Limits		
Australia	TWA (mg/m <sup>3</sup> )	<= 14 mg/m <sup>3</sup>
	TWA (ppm)	<= 10 ppm
	STEL (mg/m <sup>3</sup> )	<= 21 mg/m <sup>3</sup>
	STEL (ppm)	<= 15 ppm
Hydrogen sulphide (7783-06-4)		
OEL : Occupational Exposure Limits		
United Kingdom	WEL - LTEL - UK [mg/m <sup>3</sup> ]	7 mg/m <sup>3</sup>
	WEL - LTEL - UK [ppm]	5 ppm
	WEL - STEL - UK [mg/m <sup>3</sup> ]	14 mg/m <sup>3</sup>
	WEL - STEL - UK [ppm]	10 ppm

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration) : No data available.

**8.2. Exposure controls**

**8.2.1. Appropriate engineering controls**

: Ensure good ventilation of the work station  
 Provide adequate general and local exhaust ventilation  
 Systems under pressure should be regularly checked for leakages  
 Consider work permit system e.g. for maintenance activities

**8.2.2. Individual protection measures, e.g. personal protective equipment**

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:  
PPE compliant to the recommended EN/ISO standards should be selected
- Eye/face protection : Safety glasses  
Wear safety glasses with side shields  
Standard EN 166 - Personal eye-protection
  - Skin protection :
    - Hand protection : Wear working gloves when handling gas containers  
Standard EN 388 - Protective gloves against mechanical risk
    - Other : Wear safety shoes while handling containers  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear
  - Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask
  - Thermal hazards : None necessary

### 8.2.3. Environmental exposure controls

- : None necessary  
Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Mixture contains one or more component(s) which have the following colour(s):  
Colourless.

Odour : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.  
Mixture contains one or more component(s) which have the following odour(s):  
Rotten eggs.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH value : Not applicable for gas-mixtures.

Molar mass : Not applicable for gas-mixtures.

Melting point : Not applicable for gas-mixtures.

Boiling point : Not applicable for gas-mixtures.

Flash point : Not applicable for gas-mixtures.

Evaporation rate (ether=1) : Not applicable for gas-mixtures.

Flammability range : Non flammable.

Vapour pressure [20°C] : Not applicable.

Vapour pressure [50°C] : Not applicable.

Relative density, gas (air=1) : Lighter or similar to air.

Solubility in water : No data available

Partition coefficient n-octanol/water [log Kow] : Not applicable for gas-mixtures.

Auto-ignition temperature : Non flammable.

Viscosity [20°C] : Not applicable.

Explosive Properties : Not applicable



# 0-200PPM HYDROGEN SULPHIDE IN AIR

SDS Ref.: AL404

Oxidising Properties : Not applicable

## **9.2. Other information**

Other data : None

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below

### **10.2. Chemical stability**

: Stable under normal conditions

### **10.3. Possibility of hazardous reactions**

: None

### **10.4. Conditions to avoid**

: None

### **10.5. Incompatible materials**

: None

### **10.6. Hazardous decomposition products**

: None

## **SECTION 11: Toxicological information**

### **11.1. Information on toxicological effects**

**Acute toxicity** : Classification criteria are not met  
Toxicological effects not expected from this product if occupational exposure limit values are not exceeded

#### **Hydrogen sulphide (7783-06-4)**

LC50 inhalation rat (ppm)	356 ppm/4h
---------------------------	------------

**Skin corrosion/irritation** : No known effects from this product  
**Serious eye damage/irritation** : No known effects from this product  
**Respiratory or skin sensitisation** : No known effects from this product  
**Germ cell mutagenicity** : No known effects from this product  
**Carcinogenicity** : No known effects from this product  
**Toxic for reproduction : Fertility** : No known effects from this product  
**Toxic for reproduction : unborn child** : No known effects from this product  
**STOT-single exposure** : No known effects from this product  
**STOT-repeated exposure** : No known effects from this product  
**Aspiration hazard** : Not applicable for gases and gas mixtures

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Assessment : No ecological damage caused by this product.

### **12.2. Persistence and degradability**

Assessment : No data available.

### **12.3. Bioaccumulative potential**

Assessment : No data available.

**12.4. Mobility in soil**

Assessment : No data available.

**12.5. Results of PBT and vPvB assessment**

Assessment : Not classified as PBT or vPvB

**12.6. Other adverse effects**

Effect on ozone layer : None

Effect on the global warming : No known effects from this product.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Dispose of contents/container in accordance with licensed collector's sorting instructions  
Contact supplier if guidance is required  
May be vented to atmosphere  
Do not discharge into any place where its accumulation could be dangerous  
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at  
<http://www.eiga.org> for more guidance on suitable disposal methods

List of hazardous waste codes (from  
Commission Decision 2001/118/EC)

: 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04

**13.2. Additional information**

: None

**SECTION 14: Transport information****14.1. UN number**

UN-No. : 1956

**14.2. UN proper shipping name**

Transport by road/rail (ADR/RID) : COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)

Transport by air (ICAO-TI / IATA-DGR) : Compressed gas, n.o.s. (Nitrogen, Oxygen)

Transport by sea (IMDG) : COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)

**14.3. Transport hazard class(es)**

Labelling :



2.2 : Non-flammable, non-toxic gases

**Transport by road/rail (ADG)**

Class : 2

Hazchemcode : 2TE

Hazard identification number : 20

Tunnel Restriction : E - Passage forbidden through tunnels of category E

**Transport by air (ICAO-TI / IATA-DGR)**

Class / Div. (Sub. risk(s)) : 2.2

**Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.2

Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-V

**14.4. Packing group**

Transport by road/rail (ADR/RID) : Not applicable

Transport by air (ICAO-TI / IATA-DGR) : Not applicable

Transport by sea (IMDG) : Not applicable

**14.5. Environmental hazards**

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

**14.6. Special precautions for user****Packing Instruction(s)**

Transport by road/rail (ADR/RID) : P200

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200

Cargo Aircraft only : 200

Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency  
Before transporting product containers:  
- Ensure there is adequate ventilation  
- Ensure that containers are firmly secured  
- Ensure cylinder valve is closed and not leaking  
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted  
- Ensure valve protection device (where provided) is correctly fitted.

HAZCHEMCODE : 2TE

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

: Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Ensure all national/local regulations are observed.

**15.2. Chemical safety assessment**



: A CSA does not need to be carried out for this product  
No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Training advice : Receptacle under pressure.

### Full text of H-statements

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H330	Fatal if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
R12	Extremely flammable
R26	Very toxic by inhalation
R50	Very toxic to aquatic organisms
R8	Contact with combustible material may cause fire
F+	Extremely flammable
N	Dangerous for the environment
O	Oxidising
T+	Very toxic

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out  
Details given in this document are believed to be correct at the time of going to press  
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted