

Safety Data Sheet



0-10PPM SO₂, 0-20ppm H₂S, 0-60ppm CO, 0-1.45% CH₄, (58% LEL Pentane Equiv.), 0-15% O₂, in N₂

Date of first issue: 15/12/2016

Version: 1.0

SDS reference: AL670

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SDS no : AL670

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.
Test gas/Calibration gas.
Laboratory use.
Contact supplier for more information on uses.

Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification : Air Liquide Australia Limited
Level 9 / 380 St. Kilda Road
3004 Melbourne VIC Australia
+61 3 9697 9888
ALAEquiries@AirLiquide.com

1.4. Emergency telephone number

Emergency telephone number : 1800 812 588

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to WHS Regulation

Physical hazards : Gases under pressure : Compressed gas H280

2.2. Label elements

Classification according to WHS Regulation

Hazard pictograms :



GHS04

Signal word : Warning

Hazard statements : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

: Asphyxiant in high concentrations.

SECTION 3: Composition/information on ingredients

3.1. **Substance** : Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to WHS Regulation
Nitrogen	(CAS No) 7727-37-9 (EC no) 231-783-9 (EC index no) (REACH-no) *1	Balance	Press. Gas (Comp.), H280
Oxygen	(CAS No) 7782-44-7 (EC no) 231-956-9 (EC index no) 008-001-00-8 (REACH-no) *1	0 - 15	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Methane	(CAS No) 74-82-8 (EC no) 200-812-7 (EC index no) 601-001-00-4 (REACH-no) *1	0 - 1.45	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Carbon monoxide	(CAS No) 630-08-0 (EC no) 211-128-3 (EC index no) 006-001-00-2 (REACH-no) 01-2119480165-39	0 - 0.006	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Acute Tox. 3 (Inhalation:gas), H331 Repr. 1A, H360D STOT RE 1, H372
Hydrogen sulphide	(CAS No) 7783-06-4 (EC no) 231-977-3 (EC index no) 016-001-00-4 (REACH-no) *2	0 - 0.002	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335 Aquatic Acute 1, H400
Sulphur dioxide	(CAS No) 7446-09-5 (EC no) 231-195-2 (EC index no) 016-011-00-9 (REACH-no) 01-2119485028-34	0 - 0.001	Press. Gas (Liq.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318

Full text of R- and H-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*2: Registration deadline not expired.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.
Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Incomplete combustion may form carbon monoxide.
None that are more toxic than the product itself.

5.3. Advice for fire-fighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Use self-contained breathing apparatus.
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.
- Hazchemcode : 2TE

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

- : Try to stop release.
Evacuate area.
Monitor concentration of released product.
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Ensure adequate air ventilation.
Act in accordance with local emergency plan.
Stay upwind.

6.2. Environmental precautions

- : Try to stop release.

6.3. Methods and material for containment and cleaning up

- : Ventilate area.

6.4. Reference to other sections

- : See also sections 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**



- Safe use of the product** : The substance must be handled in accordance with good industrial hygiene and safety procedures.
 Only experienced and properly instructed persons should handle gases under pressure.
 Consider pressure relief device(s) in gas installations.
 Ensure the complete gas system was (or is regularly) checked for leaks before use.
 Do not smoke while handling product.
 Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
 Do not breathe gas.
 Avoid release of product into atmosphere.
- Safe handling of the gas receptacle** : Refer to supplier's container handling instructions.
 Do not allow backfeed into the container.
 Protect cylinders from physical damage; do not drag, roll, slide or drop.
 When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
 Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
 If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
 Never attempt to repair or modify container valves or safety relief devices.
 Damaged valves should be reported immediately to the supplier.
 Keep container valve outlets clean and free from contaminants particularly oil and water.
 Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
 Close container valve after each use and when empty, even if still connected to equipment.
 Never attempt to transfer gases from one cylinder/container to another.
 Never use direct flame or electrical heating devices to raise the pressure of a container.
 Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
 Containers should be stored in the vertical position and properly secured to prevent them from falling over.

7.2. Conditions for safe storage, including any incompatibilities

- : Observe all regulations and local requirements regarding storage of containers.
 Containers should not be stored in conditions likely to encourage corrosion.
 Container valve guards or caps should be in place.
 Containers should be stored in the vertical position and properly secured to prevent them from falling over.
 Stored containers should be periodically checked for general condition and leakage.
 Keep container below 50°C in a well ventilated place.
 Store containers in location free from fire risk and away from sources of heat and ignition.
 Keep away from combustible materials.

7.3. Specific end use(s)

- : None.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****0-10PPM SO₂, 0-20ppm H₂S, 0-60ppm CO, 0-1.45% CH₄, (58% LEL Pentane Equiv.), 0-15% O₂, in N₂**

OEL : Occupational Exposure Limits

Australia	TWA (mg/m ³)	34 mg/m ³ Carbon monoxide
	TWA (ppm)	30 ppm Carbon monoxide

Sulphur dioxide (7446-09-5)

DNEL: Derived no effect level (Workers)

Acute - local effects, inhalation	2.7 mg/m ³
Long-term - local effects, inhalation	1.3 mg/m ³

Carbon monoxide (630-08-0)

DNEL: Derived no effect level (Workers)

Acute - local effects, inhalation	100 ppm
Acute - systemic effects, inhalation	100 ppm
Long-term - local effects, inhalation	20 ppm



Long-term - systemic effects, inhalation	20 ppm
------------------------------------------	--------

Sulphur dioxide (7446-09-5)

Carbon monoxide (630-08-0)

8.2. Exposure controls

8.2.1. Appropriate engineering controls

: Provide adequate general and local exhaust ventilation.
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Oxygen detectors should be used when asphyxiating gases may be released.
Consider work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection

: Wear safety glasses with side shields.
Standard EN 166 - Personal eye-protection.

• Skin protection

- Hand protection

: Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk.

- Other

: Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

• Respiratory protection

: Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

• Thermal hazards

: None necessary.

8.2.3. Environmental exposure controls

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa
- Colour

: Gas.
: Mixture contains one or more component(s) which have the following colour(s):
Colourless.

Odour

: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.
Mixture contains one or more component(s) which have the following odour(s):
Pungent. Rotten eggs.

Odour threshold

: Odour threshold is subjective and inadequate to warn of overexposure.

pH value

: Not applicable for gas-mixtures.

Molar mass

: Not applicable for gas-mixtures.

Melting point

: Not applicable for gas-mixtures.

Boiling point

: Not applicable for gas-mixtures.

Flash point

: Not applicable for gas-mixtures.

Evaporation rate (ether=1)

: Not applicable for gas-mixtures.

Flammability range	: Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Relative density, gas (air=1)	: Lighter or similar to air.
Solubility in water	: No data available
Partition coefficient n-octanol/water [log Kow]	: Not applicable for gas-mixtures.
Auto-ignition temperature	: Non flammable.
Viscosity [20°C]	: Not applicable.
Explosive Properties	: Not applicable.
Oxidising Properties	: Not applicable.

9.2. Other information

Other data : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: None under normal use

10.4. Conditions to avoid

: Extremely high temperatures.

10.5. Incompatible materials

: None.

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Classification criteria are not met.
Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.

Sulphur dioxide (7446-09-5)	
LC50 inhalation rat (ppm)	1260 ppm/4h
Carbon monoxide (630-08-0)	
LC50 inhalation rat (ppm)	3760 ppm/1h (P200) 1300 ppm/4h
Hydrogen sulphide (7783-06-4)	
LC50 inhalation rat (ppm)	356 ppm/4h

Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.



STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

SECTION 12: Ecological information**12.1. Toxicity**

Assessment : Classification criteria are not met.

12.2. Persistence and degradability

Assessment : No data available.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : No data available.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : Contains greenhouse gas(es) not covered by Regulation (EC) 842/2006.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Contact supplier if guidance is required.
Do not discharge into any place where its accumulation could be dangerous.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at
<http://www.eiga.org> for more guidance on suitable disposal methods.

List of hazardous waste codes (from Commission Decision 2001/118/EC) : 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

: None.

SECTION 14: Transport information**14.1. UN number**

UN-No. : 1956

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : COMPRESSED GAS, N.O.S. (Nitrogen, Methane)

Transport by air (ICAO-TI / IATA-DGR) : Compressed gas, n.o.s. (Nitrogen, Methane)

Transport by sea (IMDG) : COMPRESSED GAS, N.O.S. (Nitrogen, Methane)



14.3. Transport hazard class(es)

Labelling



2.2 : Non-flammable, non-toxic gases

Transport by road/rail (ADG)

Class : 2
Hazchemcode : 2TE
Hazard identification number : 20
Tunnel Restriction : E - Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200
Transport by air (ICAO-TI / IATA-DGR)
 Passenger and Cargo Aircraft : 200
 Cargo Aircraft only : 200
Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.



0-10PPM SO₂, 0-20ppm
H₂S, 0-60ppm CO, 0-1.45%
CH₄, (58% LEL Pentane
Equiv.), 0-15% O₂, in N₂

SDS Ref.: AL670

HAZCHEMCODE : 2TE

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Training advice : Receptacle under pressure.

Full text of H-statements

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Gas 1	Flammable gases, Category 1
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 1A	Reproductive toxicity, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H330	Fatal if inhaled
H331	Toxic if inhaled
H335	May cause respiratory irritation
H360D	May damage the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
R12	Extremely flammable
R23	Toxic by inhalation
R26	Very toxic by inhalation
R34	Causes burns
R48/23	Toxic: danger of serious damage to health by prolonged exposure through inhalation
R50	Very toxic to aquatic organisms



AIR LIQUIDE

0-10PPM SO₂, 0-20ppm
H₂S, 0-60ppm CO, 0-1.45%
CH₄, (58% LEL Pentane
Equiv.), 0-15% O₂, in N₂

SDS Ref.: AL670

R61	May cause harm to the unborn child
R8	Contact with combustible material may cause fire
C	Corrosive
F+	Extremely flammable
N	Dangerous for the environment
O	Oxidising
T	Toxic
T+	Very toxic

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press.
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document