

# Safety Data Sheet



## 23.6 - 99.0 Oxygen in Nitrogen

Date of first issue: 20/06/2014

Revised date: 05/12/2016

Supersedes: 20/06/2014

Version: 1.0

SDS reference: AL711

**Danger**



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

SDS no : AL711

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use  
Test gas/Calibration gas  
Laboratory use  
Contact supplier for more information on uses

Uses advised against : Consumer use

#### 1.3. Details of the supplier of the safety data sheet

Company identification : Air Liquide Australia Limited  
Level 9 / 380 St. Kilda Road  
3004 Melbourne VIC Australia  
+61 3 9697 9888  
ALAEquiries@AirLiquide.com

#### 1.4. Emergency telephone number

Emergency telephone number : 1800 812 588

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to WHS Regulation

Physical hazards Oxidising Gases, Category 1 H270  
Gases under pressure : Compressed gas H280

#### 2.2. Label elements

##### Classification according to WHS Regulation

Hazard pictograms :



Signal word : Danger

Hazard statements : H270 - May cause or intensify fire; oxidizer.  
H280 - Contains gas under pressure; may explode if heated.

Precautionary statements

- Prevention : P220 - Keep/Store away from clothing/.../combustible materials  
P244 - Keep valves and fittings free from oil and grease
- Response : P370+P376 - In case of fire: stop leak if safe to do so
- Storage : P403 - Store in a well-ventilated place  
P410+P403 - Protect from sunlight. Store in a well-ventilated place

### 2.3. Other hazards

: None

## SECTION 3: Composition/information on ingredients

**3.1. Substance** : Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to WHS Regulation
Oxygen	(CAS No) 7782-44-7 (EC no) 231-956-9 (EC index no) 008-001-00-8 (REACH-no) *1	23.6 - 99	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Nitrogen	(CAS No) 7727-37-9 (EC no) 231-783-9 (EC index no) (REACH-no) *1	Bal	Press. Gas (Comp.), H280

Full text of R- and H-statements: see section 16

*Contains no other components or impurities which will influence the classification of the product.*

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*2: Registration deadline not expired.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- Inhalation : Remove person to fresh air and keep comfortable for breathing  
Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped
- Skin contact : Adverse effects not expected from this product  
Wash skin with plenty of water
- Eye contact : Adverse effects not expected from this product  
Rinse eyes with water as a precaution
- Ingestion : Ingestion is not considered a potential route of exposure  
Call a poison center or a doctor if you feel unwell

### 4.2. Most important symptoms and effects, both acute and delayed

: Refer to section 11

### 4.3. Indication of any immediate medical attention and special treatment needed

: None

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog  
Water spray  
Dry powder  
Foam
- Unsuitable extinguishing media : Do not use water jet to extinguish

**5.2. Special hazards arising from the substance or mixture**

- Specific hazards : Supports combustion  
Exposure to fire may cause containers to rupture/explode
- Hazardous combustion products : None that are more toxic than the product itself

**5.3. Advice for fire-fighters**

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems  
If possible, stop flow of product  
Use water spray or fog to knock down fire fumes if possible  
Move containers away from the fire area if this can be done without risk
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask  
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters
- Hazchemcode : 25

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

- : Try to stop release  
Evacuate area  
Monitor concentration of released product  
Eliminate ignition sources  
Ensure adequate air ventilation  
Act in accordance with local emergency plan  
Stay upwind

**6.2. Environmental precautions**

- : Avoid release to the environment  
Try to stop release

**6.3. Methods and material for containment and cleaning up**

- : Ventilate area

**6.4. Reference to other sections**

- : See also sections 8 and 13  
For further information refer to section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**



- Safe use of the product** :
- The substance must be handled in accordance with good industrial hygiene and safety procedures
  - Only experienced and properly instructed persons should handle gases under pressure
  - Consider pressure relief device(s) in gas installations
  - Ensure the complete gas system was (or is regularly) checked for leaks before use
  - Do not smoke while handling product
  - Keep equipment free from oil and grease
  - Use no oil or grease
  - Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt
  - Do not breathe gas
  - Avoid release of product into atmosphere.
- Safe handling of the gas receptacle** :
- Open valve slowly to avoid pressure shock
  - Refer to supplier's container handling instructions
  - Do not allow backfeed into the container
  - Protect cylinders from physical damage; do not drag, roll, slide or drop
  - When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders
  - Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use
  - If user experiences any difficulty operating cylinder valve discontinue use and contact supplier
  - Never attempt to repair or modify container valves or safety relief devices
  - Damaged valves should be reported immediately to the supplier
  - Keep container valve outlets clean and free from contaminants particularly oil and water
  - Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment
  - Close container valve after each use and when empty, even if still connected to equipment
  - Never attempt to transfer gases from one cylinder/container to another
  - Never use direct flame or electrical heating devices to raise the pressure of a container
  - Do not remove or deface labels provided by the supplier for the identification of the cylinder contents
  - Containers should be stored in the vertical position and properly secured to prevent them from falling over.

**7.2. Conditions for safe storage, including any incompatibilities**

- :
- Observe all regulations and local requirements regarding storage of containers
  - Containers should not be stored in conditions likely to encourage corrosion
  - Container valve guards or caps should be in place
  - Containers should be stored in the vertical position and properly secured to prevent them from falling over
  - Stored containers should be periodically checked for general condition and leakage
  - Keep container below 50°C in a well ventilated place
  - Segregate from flammable gases and other flammable materials in store
  - Store containers in location free from fire risk and away from sources of heat and ignition
  - Keep away from combustible materials.

**7.3. Specific end use(s)**

- : None.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

OEL (Occupational Exposure Limits) : No data available.

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration) : No data available.

**8.2. Exposure controls**

**8.2.1. Appropriate engineering controls**

- : Ensure good ventilation of the work station
- Provide adequate general and local exhaust ventilation
- Systems under pressure should be regularly checked for leakages
- Ensure exposure is below occupational exposure limits (where available)
- Gas detectors should be used when oxidising gases may be released
- Consider work permit system e.g. for maintenance activities

**8.2.2. Individual protection measures, e.g. personal protective equipment**

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
- PPE compliant to the recommended EN/ISO standards should be selected

## • Eye/face protection

- : Safety glasses
- Wear safety glasses with side shields
- Standard EN 166 - Personal eye-protection

## • Skin protection

## - Hand protection

- : Wear working gloves when handling gas containers
- Standard EN 388 - Protective gloves against mechanical risk

## - Other

- : Consider the use of flame resistant safety clothing
- Standard EN ISO 14116 - Limited flame spread materials
- Wear safety shoes while handling containers
- Standard EN ISO 20345 - Personal protective equipment - Safety footwear

## • Respiratory protection

- : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres
- Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask

## • Thermal hazards

- : None necessary

**8.2.3. Environmental exposure controls**

- : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment
- Avoid release to the environment.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

## Appearance

- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Mixture contains one or more component(s) which have the following colour(s): Colourless.

## Odour

: Odourless.

## Odour threshold

: Odour threshold is subjective and inadequate to warn of overexposure.

## pH value

: Not applicable for gas-mixtures.

## Molar mass

: Not applicable for gas-mixtures.

## Melting point

: Not applicable for gas-mixtures.

## Boiling point

: Not applicable for gas-mixtures.

## Flash point

: Not applicable for gas-mixtures.

## Evaporation rate (ether=1)

: Not applicable for gas-mixtures.

## Flammability range

: Non flammable.

## Vapour pressure [20°C]

: Not applicable.

## Vapour pressure [50°C]

: Not applicable.

Relative density, gas (air=1)	: Lighter or similar to air.
Solubility in water	: No data available
Partition coefficient n-octanol/water [log Kow]	: Not applicable for gas-mixtures.
Auto-ignition temperature	: Non flammable.
Viscosity [20°C]	: Not applicable.
Explosive Properties	: Not applicable
Oxidising Properties	: Oxidiser

**9.2. Other information**

Other data	: None
------------	--------

**SECTION 10: Stability and reactivity****10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below

**10.2. Chemical stability**

: Stable under normal conditions

**10.3. Possibility of hazardous reactions**

: Violently oxidises organic material

**10.4. Conditions to avoid**

: None

**10.5. Incompatible materials**

: Combustible materials  
May react violently with combustible materials  
May react violently with reducing agents

**10.6. Hazardous decomposition products**

: Under normal conditions of storage and use, hazardous decomposition products should not be produced

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

Acute toxicity	: No toxicological effects from this product
Skin corrosion/irritation	: No known effects from this product
Serious eye damage/irritation	: No known effects from this product
Respiratory or skin sensitisation	: No known effects from this product
Germ cell mutagenicity	: No known effects from this product
Carcinogenicity	: No known effects from this product
Toxic for reproduction : Fertility	: No known effects from this product
Toxic for reproduction : unborn child	: No known effects from this product
STOT-single exposure	: No known effects from this product
STOT-repeated exposure	: No known effects from this product
Aspiration hazard	: Not applicable for gases and gas mixtures

**SECTION 12: Ecological information****12.1. Toxicity**

Assessment : Classification criteria are not met.

#### **12.2. Persistence and degradability**

Assessment : No data available.

#### **12.3. Bioaccumulative potential**

Assessment : No data available.

#### **12.4. Mobility in soil**

Assessment : No data available.

#### **12.5. Results of PBT and vPvB assessment**

Assessment : Not classified as PBT or vPvB

#### **12.6. Other adverse effects**

Effect on ozone layer : None

Effect on the global warming : No known effects from this product.

### **SECTION 13: Disposal considerations**

#### **13.1. Waste treatment methods**

Dispose of contents/container in accordance with licensed collector's sorting instructions  
Contact supplier if guidance is required  
Do not discharge into any place where its accumulation could be dangerous  
Ensure that the emission levels from local regulations or operating permits are not exceeded  
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods

List of hazardous waste codes (from Commission Decision 2001/118/EC) : 16 05 04: Gases in pressure containers (including halons) containing dangerous substances

#### **13.2. Additional information**

: None

### **SECTION 14: Transport information**

#### **14.1. UN number**

UN-No. : 3156

#### **14.2. UN proper shipping name**

Transport by road/rail (ADR/RID) : COMPRESSED GAS, OXIDIZING, N.O.S. (Oxygen, Nitrogen)

Transport by air (ICAO-TI / IATA-DGR) : Compressed gas, oxidizing, n.o.s. (Oxygen, Nitrogen)

Transport by sea (IMDG) : COMPRESSED GAS, OXIDIZING, N.O.S. (Oxygen, Nitrogen)

#### **14.3. Transport hazard class(es)**

Labelling :



2.2 : Non-flammable, non-toxic gases  
5.1 : Oxidizing substances

**Transport by road/rail (ADG)**

Class : 2  
Hazchemcode : 25  
Hazard identification number : 25  
Tunnel Restriction : E - Passage forbidden through tunnels of category E

**Transport by air (ICAO-TI / IATA-DGR)**

Class / Div. (Sub. risk(s)) : 2.2 (5.1)

**Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.2 (5.1)  
Emergency Schedule (EmS) - Fire : F-C  
Emergency Schedule (EmS) - Spillage : S-W

**14.4. Packing group**

Transport by road/rail (ADR/RID) : Not applicable  
Transport by air (ICAO-TI / IATA-DGR) : Not applicable  
Transport by sea (IMDG) : Not applicable

**14.5. Environmental hazards**

Transport by road/rail (ADR/RID) : None.  
Transport by air (ICAO-TI / IATA-DGR) : None.  
Transport by sea (IMDG) : None.

**14.6. Special precautions for user****Packing Instruction(s)**

Transport by road/rail (ADR/RID) : P200  
Transport by air (ICAO-TI / IATA-DGR)  
    Passenger and Cargo Aircraft : 200  
    Cargo Aircraft only : 200  
Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency  
Before transporting product containers:  
- Ensure there is adequate ventilation  
- Ensure that containers are firmly secured  
- Ensure cylinder valve is closed and not leaking  
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted  
- Ensure valve protection device (where provided) is correctly fitted.

HAZCHEMCODE : 25

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**



: Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Ensure all national/local regulations are observed.

**15.2. Chemical safety assessment**: A CSA does not need to be carried out for this product  
No chemical safety assessment has been carried out**SECTION 16: Other information**

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Training advice : Receptacle under pressure.

Full text of H-statements

Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
R8	Contact with combustible material may cause fire
O	Oxidising

**DISCLAIMER OF LIABILITY**: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out  
Details given in this document are believed to be correct at the time of going to press  
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted**End of document**