

# Safety Data Sheet



## 0-5.0% Ethane in Propane

Date of first issue: 01/08/2014

Revised date: 05/12/2016

Version: 1.0

SDS reference: AL715

**Danger**



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

SDS no : AL715

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use  
Test gas/Calibration gas  
Laboratory use  
Contact supplier for more information on uses

Uses advised against : Consumer use

#### 1.3. Details of the supplier of the safety data sheet

Company identification : Air Liquide Australia Limited  
Level 9 / 380 St. Kilda Road  
3004 Melbourne VIC Australia  
+61 3 9697 9888  
ALAEquiries@AirLiquide.com

#### 1.4. Emergency telephone number

Emergency telephone number : 1800 812 588

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to WHS Regulation

Physical hazards	Flammable gases, Category 1	H220
	Gases under pressure : Liquefied gas	H280

#### 2.2. Label elements

##### Classification according to WHS Regulation

Hazard pictograms :



Signal word : Danger

Hazard statements : H220 - Extremely flammable gas.  
H280 - Contains gas under pressure; may explode if heated.

Precautionary statements

- Prevention : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Response : P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely  
P381 - Eliminate all ignition sources if safe to do so
- Storage : P403 - Store in a well-ventilated place  
P410+P403 - Protect from sunlight. Store in a well-ventilated place

**2.3. Other hazards**

: None

**SECTION 3: Composition/information on ingredients**

**3.1. Substance** : Not applicable

**3.2. Mixture**

Name	Product identifier	%	Classification according to WHS Regulation
Propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	Bal	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Ethane	(CAS No) 74-84-0 (EC no) 200-814-8 (EC index no) 601-002-00-X (REACH-no) *2	0 - 5	Flam. Gas 1, H220 Press. Gas (Comp.), H280

Full text of R- and H-statements: see section 16

*Contains no other components or impurities which will influence the classification of the product.*

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*2: Registration deadline not expired.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

- Inhalation : Remove person to fresh air and keep comfortable for breathing  
Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped
- Skin contact : For liquid spillage - flush with water for at least 15 minutes  
Wash skin with plenty of water
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes  
Rinse eyes with water as a precaution
- Ingestion : Ingestion is not considered a potential route of exposure  
Call a poison center or a doctor if you feel unwell

**4.2. Most important symptoms and effects, both acute and delayed**

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation  
Refer to section 11

**4.3. Indication of any immediate medical attention and special treatment needed**

: None

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**



- Suitable extinguishing media : Water spray or fog  
Water spray  
Dry powder  
Foam
- Unsuitable extinguishing media : Carbon dioxide  
Do not use water jet to extinguish

**5.2. Special hazards arising from the substance or mixture**

- Specific hazards : Exposure to fire may cause containers to rupture/explode
- Hazardous combustion products : Incomplete combustion may form carbon monoxide

**5.3. Advice for fire-fighters**

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems  
If possible, stop flow of product  
Use water spray or fog to knock down fire fumes if possible  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire  
Move containers away from the fire area if this can be done without risk
- Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus  
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask  
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters
- Hazchemcode : 2YE

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

- : Try to stop release  
Evacuate area  
Consider the risk of potentially explosive atmospheres  
Eliminate ignition sources  
Ensure adequate air ventilation  
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous  
Act in accordance with local emergency plan  
Stay upwind

**6.2. Environmental precautions**

- : Avoid release to the environment  
Try to stop release

**6.3. Methods and material for containment and cleaning up**

- : Ventilate area

**6.4. Reference to other sections**

- : See also sections 8 and 13  
For further information refer to section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**



- Safe use of the product : The substance must be handled in accordance with good industrial hygiene and safety procedures  
Only experienced and properly instructed persons should handle gases under pressure  
Consider pressure relief device(s) in gas installations  
Ensure the complete gas system was (or is regularly) checked for leaks before use  
Do not smoke while handling product  
Protect eyes, face and skin from liquid splashes  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt  
Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment  
Purge air from system before introducing gas  
Take precautionary measures against static discharge  
Keep away from ignition sources (including static discharges)  
Consider the use of only non-sparking tools  
Do not breathe gas  
Avoid release of product into atmosphere.
- Safe handling of the gas receptacle : Refer to supplier's container handling instructions  
Do not allow backfeed into the container  
Protect cylinders from physical damage; do not drag, roll, slide or drop  
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders  
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use  
If user experiences any difficulty operating cylinder valve discontinue use and contact supplier  
Never attempt to repair or modify container valves or safety relief devices  
Damaged valves should be reported immediately to the supplier  
Keep container valve outlets clean and free from contaminants particularly oil and water  
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment  
Close container valve after each use and when empty, even if still connected to equipment  
Never attempt to transfer gases from one cylinder/container to another  
Never use direct flame or electrical heating devices to raise the pressure of a container  
Do not remove or deface labels provided by the supplier for the identification of the cylinder contents  
Containers should be stored in the vertical position and properly secured to prevent them from falling over.

### **7.2. Conditions for safe storage, including any incompatibilities**

- : Observe all regulations and local requirements regarding storage of containers  
Containers should not be stored in conditions likely to encourage corrosion  
Container valve guards or caps should be in place  
Containers should be stored in the vertical position and properly secured to prevent them from falling over  
Stored containers should be periodically checked for general condition and leakage  
Keep container below 50°C in a well ventilated place  
Store containers in location free from fire risk and away from sources of heat and ignition  
Keep away from combustible materials  
Segregate from oxidant gases and other oxidants in store  
All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

### **7.3. Specific end use(s)**

- : None.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

OEL (Occupational Exposure Limits) : No data available.

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration) : No data available.

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

- : Ensure good ventilation of the work station
- Provide adequate general and local exhaust ventilation
- Systems under pressure should be regularly checked for leakages
- Ensure exposure is below occupational exposure limits (where available)
- Keep concentrations well below lower explosion limits
- Gas detectors should be used when flammable gases/vapours may be released
- Consider work permit system e.g. for maintenance activities

### 8.2.2. Individual protection measures, e.g. personal protective equipment

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:  
PPE compliant to the recommended EN/ISO standards should be selected

#### • Eye/face protection

- : Safety glasses
- Wear safety glasses with side shields
- Wear goggles and a face shield when transfilling or breaking transfer connections
- Standard EN 166 - Personal eye-protection

#### • Skin protection

##### - Hand protection

- : Wear working gloves when handling gas containers
- Standard EN 388 - Protective gloves against mechanical risk

##### - Other

- : Consider the use of flame resistant anti-static safety clothing
- Standard EN ISO 14116 - Limited flame spread materials
- Standard EN ISO 1149-5 - Protective clothing: Electrostatic properties
- Wear safety shoes while handling containers
- Standard EN ISO 20345 - Personal protective equipment - Safety footwear

#### • Respiratory protection

- : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres
- Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask

#### • Thermal hazards

- : Wear cold insulating gloves when transfilling or breaking transfer connections
- Standard EN 511 - Cold insulating gloves

### 8.2.3. Environmental exposure controls

- : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment
- Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Mixture contains one or more component(s) which have the following colour(s):  
Colourless.

#### Odour

- : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.
- Mixture contains one or more component(s) which have the following odour(s):  
Stenchant often added. Sweetish.

#### Odour threshold

- : Odour threshold is subjective and inadequate to warn of overexposure.

#### pH value

- : Not applicable for gas-mixtures.

#### Molar mass

- : Not applicable for gas-mixtures.

#### Melting point

- : Not applicable for gas-mixtures.

#### Boiling point

- : Not applicable for gas-mixtures.

Flash point	: Not applicable for gas-mixtures.
Evaporation rate (ether=1)	: Not applicable for gas-mixtures.
Flammability range	: Flammability range not available.
Vapour pressure [20°C]	: No reliable data available.
Vapour pressure [50°C]	: No reliable data available.
Relative density, gas (air=1)	: Heavier than air.
Solubility in water	: No data available
Partition coefficient n-octanol/water [log Kow]	: Not applicable for gas-mixtures.
Auto-ignition temperature	: Not known.
Viscosity [20°C]	: Not applicable.
Explosive Properties	: Not applicable
Oxidising Properties	: Not applicable

**9.2. Other information**

Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level
------------	---

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below  
Extremely flammable gas

**10.2. Chemical stability**

: Stable under normal conditions

**10.3. Possibility of hazardous reactions**

: May react violently with oxidants  
Can form explosive mixture with air

**10.4. Conditions to avoid**

: Keep away from heat/sparks/open flames/hot surfaces. – No smoking  
Avoid contact with hot surfaces  
Heat  
No flames, no sparks. Eliminate all sources of ignition

**10.5. Incompatible materials**

: May react violently with oxidants

**10.6. Hazardous decomposition products**

: Under normal conditions of storage and use, hazardous decomposition products should not be produced

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

<b>Acute toxicity</b>	: Classification criteria are not met Toxicological effects not expected from this product if occupational exposure limit values are not exceeded
-----------------------	--

**Propane (74-98-6)**

LC50 inhalation rat (ppm)	20000 ppm/4h
---------------------------	--------------

<b>Skin corrosion/irritation</b>	: No known effects from this product
<b>Serious eye damage/irritation</b>	: No known effects from this product
<b>Respiratory or skin sensitisation</b>	: No known effects from this product
<b>Germ cell mutagenicity</b>	: No known effects from this product

<b>Carcinogenicity</b>	: No known effects from this product
<b>Toxic for reproduction : Fertility</b>	: No known effects from this product
<b>Toxic for reproduction : unborn child</b>	: No known effects from this product
<b>STOT-single exposure</b>	: No known effects from this product
<b>STOT-repeated exposure</b>	: No known effects from this product
<b>Aspiration hazard</b>	: Not applicable for gases and gas mixtures

## SECTION 12: Ecological information

### 12.1. Toxicity

Assessment : Classification criteria are not met.

### 12.2. Persistence and degradability

Assessment : No data available.

### 12.3. Bioaccumulative potential

Assessment : No data available.

### 12.4. Mobility in soil

Assessment : No data available.

### 12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB

### 12.6. Other adverse effects

Effect on ozone layer : None

Effect on the global warming : No known effects from this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Dispose of contents/container in accordance with licensed collector's sorting instructions  
Contact supplier if guidance is required  
Do not discharge into areas where there is a risk of forming an explosive mixture with air.  
Waste gas should be flared through a suitable burner with flash back arrestor  
Do not discharge into any place where its accumulation could be dangerous  
Ensure that the emission levels from local regulations or operating permits are not exceeded  
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods

List of hazardous waste codes (from Commission Decision 2001/118/EC) : 16 05 04: Gases in pressure containers (including halons) containing dangerous substances

### 13.2. Additional information

: None

## SECTION 14: Transport information

### 14.1. UN number

UN-No. : 1965

### 14.2. UN proper shipping name

**Transport by road/rail (ADR/RID)** : HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S. (Propane, Ethane)

**Transport by air (ICAO-TI / IATA-DGR)** : Hydrocarbon gas mixture, liquefied, n.o.s. (Propane, Ethane)

**Transport by sea (IMDG)** : HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S. (Propane, Ethane)

#### **14.3. Transport hazard class(es)**

**Labelling**



2.1 : Flammable gases

#### **Transport by road/rail (ADG)**

Class : 2  
Hazchemcode : 2YE  
Hazard identification number : 23  
Tunnel Restriction : B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage : Passage forbidden through tunnels of category D and E

#### **Transport by air (ICAO-TI / IATA-DGR)**

Class / Div. (Sub. risk(s)) : 2.1

#### **Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.1  
Emergency Schedule (EmS) - Fire : F-D  
Emergency Schedule (EmS) - Spillage : S-U

#### **14.4. Packing group**

Transport by road/rail (ADR/RID) : Not applicable  
Transport by air (ICAO-TI / IATA-DGR) : Not applicable  
Transport by sea (IMDG) : Not applicable

#### **14.5. Environmental hazards**

Transport by road/rail (ADR/RID) : None.  
Transport by air (ICAO-TI / IATA-DGR) : None.  
Transport by sea (IMDG) : None.

#### **14.6. Special precautions for user**

##### **Packing Instruction(s)**

Transport by road/rail (ADR/RID) : P200  
Transport by air (ICAO-TI / IATA-DGR)  
    Passenger and Cargo Aircraft : Forbidden  
    Cargo Aircraft only : 200  
Transport by sea (IMDG) : P200



Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment  
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency  
 Before transporting product containers:  
 - Ensure there is adequate ventilation  
 - Ensure that containers are firmly secured  
 - Ensure cylinder valve is closed and not leaking  
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted  
 - Ensure valve protection device (where provided) is correctly fitted.

HAZCHEMCODE : 2YE

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

: Not applicable.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**National regulations**

Ensure all national/local regulations are observed.

**15.2. Chemical safety assessment**

: A CSA does not need to be carried out for this product  
 No chemical safety assessment has been carried out

**SECTION 16: Other information**

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Training advice : Ensure operators understand the flammability hazard. Receptacle under pressure.

Full text of H-statements

Flam. Gas 1	Flammable gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
R12	Extremely flammable
F+	Extremely flammable

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out  
 Details given in this document are believed to be correct at the time of going to press  
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted

**End of document**